

Project: \_\_\_\_\_  
 Type: \_\_\_\_\_  
 Model: \_\_\_\_\_

**DESCRIPTION**

The Luminoso 2" LED Remodel housing is perfect for low to medium height ceilings in residential, and light commercial applications. The air tight construction reduces energy costs by preventing air flow between occupied conditioned spaces and unvented areas.

**HOUSING**

Integral thermal protector to guard against improper lamping and installation. Trim is secured with internal locking mechanism. Galvanized steel construction. The housing can be removed from the plaster to provide access to the junction box.

**DRIVER**

120-277V built in electronic Direct Current U.L. Listed driver mounted away from LED Array for cool operation and end-of-life modularity. The Luminoso 2" housing and trim combination are standard with 0-10V dimming.

**JUNCTION BOX**


4 gauge pre-wired aluminum Junction Box. 4 cubic-inch for a maximum of (4) #12 AWG wires. Contains one 1/8", six 7/8" knockouts and four conduit pryouts with strain relief.

**FEATURES**


- UL Listed for Damp Locations
- UL Listed for Feed Through
- Warranty: 5 year limited warranty
- Certified under ASTM-E283 for Air Tight Construction
- Built in Driver 120-277V (0-10V Dimming)




**COMPATIBLE TRIMS**




DL 2HD RS



DL 2HD RG





DL 2HD SS



DL 2HD SG

**DIMENSIONS**



Dimensions and values shown are nominal. LuminosoLED continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.

